

5V Relay Module

The Relay Module is used to control AC or DC circuits. The relay acts as a switch that responds to a signal received from the Arduino. It has an integrated LED that indicates if the signal is high or low.

On the control side of the board there are 3 pins for signal, power and ground. On the load side there are 3 contacts, NC (Normally Closed), Common and NO (Normally Open).

TTL Control Signal	5VDC to 12VDC
Maximum AC	10A 250VAC
Maximum DC	10A 30VDC
Contact type	NC and NO




Pinout and Connection to Arduino

For the DC part of the circuit connect S (signal) to pin 10 on the Arduino, also connect the Power line (+) and ground (-) to +5 and GND respectively.

On the AC side connect your feed to Common (middle contact) and use NC or NO according to your needs.

NO (Normally Open) will get power when (S) is high, NC (Normally Closed) gets disconnected when (S) is high.

Always be very careful when experimenting with AC, electrical shock can result in serious injuries!



Arduino Example Sketch

The following Arduino sketch will turn the relay on/off every second. We'll connect a desk lamp to the relay using the NO (Normally Open) connection so the lamp is off when the relay is off. Running the sketch will cause the lamp to light up intermittently.

```
int relay = 10;  //Pin 10

void setup()
{
    pinMode(relay,OUTPUT);  // Define the port attribute as output
}

void loop()
{
    digitalWrite(relay,HIGH);  // turn the relay ON
    delay(1000);
    digitalWrite(relay,LOW);   // turn the relay OFF
    delay(1000);
}
```