


NPN SILICON PLANAR EPITAXIAL TRANSISTORS




BC237 A, B, C
BC238 A, B, C
BC239 B, C

TO-92
Plastic Package

General Purpose Transistor, Best Suited For use In Driver Stages Of Audio Amplifiers, Low Noise Input Stages of Tape Recorders. Hi-Fi Amplifiers , Signal Processing Circuits Of Television Receivers.

DESCRIPTION	SYMBOL	BC237	BC238	BC239	UNITS
Collector -Emitter Voltage	V_{CEO}	45	25	25	V
Collector -Emitter Voltage	V_{CES}	50	30	30	V
Emitter -Base Voltage	V_{EBO}	6	5	5	V
Collector Current Continuous	I_C		100		mA
Power Dissipation@ Ta=25°C	P_D		350		mW
Derate Above 25°C			2.8		mW/°C
Power Dissipation@ Tc=25°C	P_D		1		W
Derate Above 25°C			8		mW/°C
Operating And Storage Junction Temperature Range	T_j, T_{stg}		-55 to +150		°C
THERMAL RESISTANCE					
Junction to ambient	$R_{th(j-a)}$		357		°C/W
Junction to case	$R_{th(j-c)}$		125		°C/W

NPN SILICON PLANAR EPITAXIAL TRANSISTORS




BC237 A, B, C
BC238 A, B, C
BC239 B, C

TO-92
Plastic Package

ELECTRICAL CHARACTERISTICS (Ta=25°C Unless Specified Otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNITS
Collector Emitter Voltage						
BC237	V_{CEO}	$I_C=2mA, I_B=0$	45			V
BC238			25			V
BC239			25			V
EmitterBase Voltage						
BC237	V_{EBO}	$I_E=100\mu A, I_C=0$	6			V
BC238, BC239			5			V
CollectorCut off Current						
BC238, BC239	I_{CES}	$V_{CE}=30V, V_{BE}=0$			15	nA
BC237		$V_{CE}=50V, V_{BE}=0$			15	nA
BC238, BC239		$V_{CE}=30V, V_{BE}=0$ $T_a=125^\circ C$			4	μA
BC237		$V_{CE}=50V, V_{BE}=0$ $T_a=125^\circ C$			4	μA
DC Current Gain						
A	h_{FE}	$I_C=10\mu A, V_{CE}=5V$		90		
B				150		
C				270		
BC237, BC238, BC239		$I_C=2mA, V_{CE}=5V$	120		800	
A			120	170	220	
B			200	290	460	
C			380	500	800	
A		$I_C=100mA, V_{CE}=5V^*$		120		
B				180		
C				300		
Collector Emitter Saturation Voltage						
BC237, BC239	$V_{CE(sat)}$	$I_C=10mA, I_B=0.5mA$		0.07	0.2	V
		$I_C=100mA, I_B=5mA^*$		0.2	0.6	V
BC238					0.8	V
Base Emitter Saturation Voltage						
	$V_{BE(sat)}$	$I_C=10mA, I_B=0.5mA$		0.6	0.83	V
		$I_C=100mA, I_B=0.5mA^*$			1.05	V
Base Emitter On Voltage						
	$V_{BE(on)}$	$I_C=100\mu A, V_{CE}=5V$		0.5		V
		$I_C=2mA, V_{CE}=5V$	0.55	0.62	0.7	V
		$I_C=100mA, V_{CE}=5V$		0.83		V

NPN SILICON PLANAR EPITAXIAL TRANSISTORS



BC237 A, B, C
BC238 A, B, C
BC239 B, C

TO-92
Plastic Package

ELECTRICAL CHARACTERISTICS (Ta=25°C Unless Specified Otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNITS
DYNAMIC CHARACTERISTICS						
Transition Frequency						
BC237	f_T	$I_C=0.5mA, V_{CE}=3V$ $f=100MHz$		100		MHz
BC238				120		
BC239				140		
BC237		$I_C=10mA, V_{CE}=5V$ $f=100MHz$	150	200		MHz
BC238			150	240		
BC239			150	280		
Collector Output Capacitance	C_{ob}	$V_{CB}=10V, I_E=0$ $f=1MHz$			4.50	pF
Emitter Input Capacitance	C_{ib}	$V_{EB}=0.5V, I_E=0$ $f=1MHz$		8.0		pF
Noise Figure						
BC237, BC238	NF	$V_{CE}=5V, I_C=0.2mA$ $R_S=2KW, f=1KHz$		2	10	dB
BC239		$f=200Hz$		2	4	dB
BC239		$I_C=0.2mA, V_{CE}=5V$ $R_S=2KW, f=30KHz$ to 15KHz		2	4	dB



*Pulse Condition: Pulse Width 300us, Duty Cycle 2%.

BC237 A, B, C
BC238 A, B, C
BC239 B, C

TO-92
Plastic Package

TO-92 Plastic Package

TO-92 Transistors on Tape and Ammo Pack




All dimensions in mm unless specified otherwise

ITEM	SYMBOL	SPECIFICATION				REMARKS
		MIN.	NOM.	MAX.	TOL.	
BODY WIDTH	A1	4.0		4.8		CUMULATIVE PITCH ERROR 1.0 mm/20 PITCH
BODY HEIGHT	A	4.8		5.2		
BODY THICKNESS	T	3.9		4.2		
PITCH OF COMPONENT	P		12.7		±1	
FEED HOLE PITCH	Po		12.7		±0.3	
FEED HOLE CENTRE TO COMPONENT CENTRE	P2		6.35		±0.4	TO BE MEASURED AT BOTTOM OF CLINCH
DISTANCE BETWEEN OUTER LEADS	F		5.08		+0.6 -0.2	AT TOP OF BODY
COMPONENT ALIGNMENT	Δh		0	1		
TAPE WIDTH	W		18		±0.5	
HOLD-DOWN TAPE WIDTH	Wo		6		±0.2	
HOLE POSITION	W1		9		+0.7 -0.5	
HOLD-DOWN TAPE POSITION	W2		0.5		±0.2	±1 0.3 - 0.6
LEAD WIRE CLINCH HEIGHT	Ho		16		±0.5	
COMPONENT HEIGHT	H1			23.25		
LENGTH OF SNIPPED LEADS	L			11.0		
FEED HOLE DIAMETER	Do		4		±0.2	
TOTAL TAPE THICKNESS	t			1.2		
LEAD - TO - LEAD DISTANCEF1,	F2		2.54		+0.4 -0.1	
CLINCH HEIGHT	H2			3		
PULL - OUT FORCE	(P)	6N				

NOTES

1. MAXIMUM ALIGNMENT DEVIATION BETWEEN LEADS NOT TO BE GREATER THAN 0.2 mm.
2. MAXIMUM NON-CUMULATIVE VARIATION BETWEEN TAPE FEED HOLES SHALL NOT EXCEED 1 mm IN 20 PITCHES.
3. HOLDDOWN TAPE NOT TO EXCEED BEYOND THE EDGE(S) OF CARRIER TAPE AND THERE SHALL BE NO EXPOSURE OF ADHESIVE.
4. NO MORE THAN 3 CONSECUTIVE MISSING COMPONENTS ARE PERMITTED.
5. A TAPE TRAILER, HAVING AT LEAST THREE FEED HOLES ARE REQUIRED AFTER THE LAST COMPONENT.
6. SPLICES SHALL NOT INTERFERE WITH THE SPROCKET FEED HOLES.

All diminsions in mm.



PIN CONFIGURATION

1. EMITTER
2. BASE
3. COLLECTOR

Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-92 Bulk	1K/polybag	200 gm/1K pcs	3" x 7.5" x 7.5"	5K	17" x 15" x 13.5"	80K	23 kgs
TO-92 T&A	2K/ammo box	645 gm/2K pcs	12.5" x 8" x 1.8"	2K	17" x 15" x 13.5"	32K	12.5 kgs

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of

Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone + 91-11-579 6150 Fax + 91-11-579 9569, 579 5290

e-mail sales@cdil.com www.cdil.com