



SINGLE BUILT-IN CHARGER

USB-C™ 60 W

Experience the impressive performance of the Single USB-C™ charger with up to 60 W of power, revolutionising charging in caravans, boats and motorhomes! The advanced USB Power Delivery technology of the charger allows for a powerful and lightning-fast charging of tablets, notebooks and smartphones.

With the practical, symmetrical USB-C™ connector becoming the standard port of the future, the charger already establishes your top-speed charging platform today.

FEATURES

- Lightning-fast charging via USB-C™ port with Power Delivery (60 W)
- Intelligent Fast Charging
- Easy installation and compatibility with the Berker and Inprojal / CBE switch ranges
- Suitable for wall thicknesses up to 17 mm
- High level of safety: protection against short circuits, overvoltage and high temperatures
- With Tyco plug or open cable ends with 200 mm cable each

RIGHT TO REPAIR 

wentronic SOLUTIONS

VARIANTS


ITEM	65580 ●	65579 ●	74055 ○
MODEL	WTS-E 1 C QC 3 PD 60 W + Tyco connector	WTS-E 1 C QC 3 PD 60 W	
INSTALLATION	with Tyco connector no. 180908	with open ends, tin-plated	with open ends, tin-plated
CABLE LENGTH	200 mm	200 mm	200 mm

TECHNICAL DATA

OUTPUT POWER	60 W
CURRENT IN STAND-BY MODE	≤ 2 mA
NOMINAL INPUT VOLTAGE	12 – 24 V $\overline{=}$
DIMENSIONS	Ø front: 36 mm, Ø chassis: 27 mm, depth: 55 mm
WEIGHT	42 g
OPERATING TEMPERATURE	-20 °C – +80 °C
STORAGE TEMPERATURE	-40 °C – +90 °C
COMPATIBLE	with current smartphones, tablets, notebooks that support USB Power Delivery or Quick Charge
STANDARDS AND CERTIFICATIONS	CE, UKCA EN 55032:2015, EN 55035:2017, EN 50498:2011 RoHS, REACH ECE-R10 Type Approval FMVSS 201 (compliance tests - Upper Interior Head Impact Protection) RCM (AUS/NZ)



CONNECTIONS AND FAST-CHARGING TECHNOLOGY

	 USB-C™ reversible connector
TOTAL POWER	5.0 V $\overline{=}$ max. 3.0 A (15 W) 9.0 V $\overline{=}$ max. 2.0 A (27 W) 12.0 V $\overline{=}$ max. 3.0 A (36 W) 15.0 V $\overline{=}$ max. 3.0 A (45 W) 20.0 V $\overline{=}$ max. 3.0 A (60 W)
FAST-CHARGING TECHNOLOGY	PD 3.0 PD 2.0 PPS BC1.2 QC 4+ QC 3+ QC 3.0 QC 2.0 FCP
LIFETIME IN INSERTION AND REMOVAL CYCLES	approx. 10,000