



F&F Filipowski sp.k., ul. Konstantinowska 79/81, 95-200 Pabianice, tel.: +48 (42) 214 90 37, e-mail: biuro@fif.com.pl, www.fif.com.pl



PK-1P-24V

Electromagnetic relay

Index: PK-1P-24V

Contact configuration 1xNO/NC. Load current 16 A. Supply voltage 24 V AC/DC.

Electromagnetic relay in single-module casing intended for direct assembly on the TH-35 bus bar.



5 908312 595632 >

FUNCTIONING

DESCRIPTION

Functioning

Application of the power supply voltage to the relay's coil results in a shift of the contact. After the decay of the voltage in question, the contact returns to the initial position.

Order labelling method:

eg. **PK-1P 24V** ----- supply voltage

TECHNICAL DATA

Complete with socket	No
With detachable clamps	No
With LED indication	Yes
Rated control supply voltage AC 50 Hz	24-24 V
Rated control supply voltage DC	24-24 V
Number of contacts as change-over contact	1

With forced-guided contacts	No
Height	90 mm
Depth	65 mm
Type of electric connection	Screw connection
Type of switch contact	Single contact
Degree of protection (IP)	IP20
Operating voltage AC 50 Hz	24-24 V
Operating voltage DC	24-24 V
Nominal current	16 A
Width	17.6 mm
Voltage type for actuating	AC/DC
Drive, switching attitude	Mono stable
Voltage type (operating voltage)	AC/DC
Nominal current	16 mA

Manual

CE Declaration