



DUAL BUILT-IN CHARGER

USB-C™

Always fully charged. The dual USB-C™ charger as the future uniform standard for charging sockets can be installed in no time at all - in motorhomes, caravans and boats.

The universal charger charges all mobile devices such as smartphones, tablets, digital cameras, headphones or mobile speakers.

FEATURES

- With USB-C™ connection for fast and easy charging
- Charges smartphones 50 % faster than products with a USB-A port from other manufacturers
- Easy to install and compatible with Berker and Inprojal switch ranges
- Suitable for wall thicknesses up to 17 mm
- Safe due to rounded edges, protection against short circuits, overvoltage, high temperatures. Dust protection optional.
- With Tyco plug or open cable ends with 200 mm cable each
- Complements the on-board equipment in black or white

VARIANTS


ITEM	60377 ● 60569 ○	60378 ● 60570 ○
MODEL	WTS-E 2 C QC 3 PD WTS-E 2 C QC 3 PD white	
INSTALLATION	with Tyco connector no. 180908	with open ends, tin-plated
CABLE LENGTH	200 mm	200 mm

TECHNICAL DATA

OUTPUT POWER	2 x 18 W
CURRENT IN STAND-BY MODE	≤ 2 mA
NOMINAL INPUT VOLTAGE	12 - 24 V $\overline{=}$
DIMENSIONS	Ø front: 36 mm, Ø chassis: 27 mm, depth: 44.5 mm
WEIGHT	27 g
OPERATING TEMPERATURE	-20 °C - +70 °C
STORAGE TEMPERATURE	-40 °C - +90 °C
COMPATIBLE	with current smartphones and tablets
STANDARDS AND CERTIFICATIONS	CE, UKCA EN 55032:2015, EN 55035:2017, EN 50498:2011 RoHS, REACH ECE-R10 Type Approval FMVSS 201 (compliance tests - Upper Interior Head Impact Protection)



CONNECTIONS AND FAST-CHARGING TECHNOLOGY

	 reversible connector						
TOTAL POWER	<table border="0"> <tr> <td>5.0 V $\overline{=}$</td> <td>max. 3.0 A (15 W)</td> </tr> <tr> <td>9.0 V $\overline{=}$</td> <td>max. 2.0 A (18 W)</td> </tr> <tr> <td>12.0 V $\overline{=}$</td> <td>max. 1.5 A (18 W)</td> </tr> </table>	5.0 V $\overline{=}$	max. 3.0 A (15 W)	9.0 V $\overline{=}$	max. 2.0 A (18 W)	12.0 V $\overline{=}$	max. 1.5 A (18 W)
5.0 V $\overline{=}$	max. 3.0 A (15 W)						
9.0 V $\overline{=}$	max. 2.0 A (18 W)						
12.0 V $\overline{=}$	max. 1.5 A (18 W)						
FAST-CHARGING TECHNOLOGY	PD 3.0 QC 4.0 QC 3.0 QC 2.0 FCP DCP BC 1.2 AFC SCP PE 1.1 SFCP						
LIFETIME IN INSERTION AND REMOVAL CYCLES	approx. 10,000						