

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 14/02/2025 Revision date: 28/08/2024 Supersedes version of: 30/08/2023 Version: 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : POSITIV 20

UFI : W44X-58KU-S00W-AUC1

Product code : BDS000793AE Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Photo-sensitive lacquer

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V. Touwslagerstraat 1 9240 Zele

Belgium

T +32(0)52/45.60.11, F +32(0)52/45.00.34 hse@crcind.com, www.crcind.com

1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11

Office hours: 9-17h CET

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Hazardous to the aquatic environment – Chronic Hazard, H412

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





GHS02 GHS07

Signal word (CLP) : Dange

Contains : n-butyl acetate;1-methoxy-2-propanol; monopropylene glycol methyl ether;2-methoxy-1-

methylethyl acetate;acetone; propan-2-one; propanone

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/eye protection.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128- 37	25 – 50	Flam. Gas 1, H220 Press. Gas (Liq.), H280
acetone; propan-2-one; propanone substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336
1-methoxy-2-propanol; monopropylene glycol methyl ether substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435- 35	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
n-butyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-	1 – 5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
1-Naphthalenesulfonic acid, 6-diazo-5,6-dihydro-5-oxo-, ester with phenyl(2,3,4-trihydroxyphenyl)methanone	CAS-No.: 68510-93-0 EC-No.: 270-931-7 REACH-no: 01-2120753804- 50	1 – 5	Flam. Sol. 1, H228 Self-react. C, H242 Skin Irrit. 2, H315 Aquatic Chronic 3, H412

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
C.I. Basic Violet 3; 4-[4,4'-bis(dimethylamino) benzhydrylidene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium chloride substance listed on REACH Candidate List ([4-[4,4'-bis(dimethylamino) benzhydrylidene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium chloride (C.I. Basic Violet 3))	CAS-No.: 548-62-9 EC-No.: 208-953-6 EC Index-No.: 612-204-00-2 REACH-no: 01-2119539680- 37	< 0,05	Carc. 2, H351 Acute Tox. 4 (Oral), H302 (ATE=670 mg/kg bodyweight) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop,

get medical attention.

First-aid measures after skin contact : Wash skin with plenty of water. Seek medical attention if irritation develops.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Call a physician immediately. Seek medical attention if irritation

develops.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard

firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it

with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to

remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good

industrial hygiene and safety procedures.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated

place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

dimethyl ether (115-10-6)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name Dimethylether

Safety Data Sheet

directly lether (115-10-6) IDEL TWA 1920 mg/m² Regulatory reference coMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits VEL TWA 2020 mg/m² 1000 ppm 1000 ppm Regulatory reference Koralidijk besluit/krété royal 16/11/2023 n-butyl acetate (123-98-4) EU - Indicatév Occupational Exposure Limit (100-1) EU - Indicatév Occupational Exposure Limit (100-1) 21 mg/m² 102 L TWA 24 mg/m² 105 ppm Regulatory reference 24 mg/m² 105 ppm Regulatory reference COMINISION DIRECTIVE (EU) 2019/1831 Bo ppm Regulatory reference Acétate de noburly et n. Butylacetant Départementement (100-1) Départementementementementementementementeme			
Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Oxyde de direkthyle # Dimethylether DEL TWA 1920 mg/m³ 1000 ppm Regulatory reference Regulatory reference Koninklijk besluit/Anétér royal 16/11/2023 n-butyl acetate (123-86-4) ************************************	dimethyl ether (115-10-6)		
Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits DEL TWA 1920 mg/m² Regulatory reference Koninklijk bealuit/Amêté royal 16/11/2023 n-butyl acetate (123-86-4) Tombutyl acetate (123-86-4) EU - Indicative Occupational Exposure Limit (IOEL)* EU - Indicative Occupational Exposure Limit (IOEL)* Local name n-Butyl acetate 10EL TWA 241 mg/m² 60 ppm 60 ppm Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Belgium - Occupational Exposure Limits Tomp Local name Acétate de n-Butyle # n-Butylacetaat OEL TWA 238 mg/m² 50 ppm 50 ppm CEL TWA 248 mg/m² 50 ppm 50 ppm CEL TWA 250 ppm OEL TWA 50 ppm Regulatory reference Acétate de n-Butyle # n-Butylacetaat OEL STEL 712 mg/m² 100 ppm Tomp Regulatory reference Acétate de n-Butyle # n-Butylacetaat EU - Indicativo Occupational Exposure Limit Indicative forçal 16/11/2023	IOEL TWA	1920 mg/m³	
Belgium - Occupational Exposure Limits Oxyde de diméthyle # Dimethylether OEL TWA 1920 mg/m³ 1000 ppm 1000 ppm Regulatory reference Koninkilijk beskult/Arrêté royal 18/11/2023 n-butyl acetate (123-86-4) EU - Indicative Occupational Exposure Limit (IOEL TWA) 241 mg/m³ 241 mg/m³ 1002 TWA 241 mg/m³ 1004 TWA 273 mg/m³ 1004 TWA 723 mg/m³ 1004 TWA 240 ppm Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Belgium - Occupational Exposure Limits Local name Acétate de n-butyle 4 n-Butylacetaat 0EL TWA 238 mg/m³ 50 ppm 0EL STEL 712 mg/m³ 150 ppm Regulatory reference Koninklijk beskuit/Arrête royal 18/11/2023 Twenty-2-propanol; monopropylone glycut EU - Indicative Occupational Exposure Limit (IOEL) EU - Indicative Occupational Exposure Limit (IOEL) EU - Indicative Occupational Exposure Limit (IOEL) 100 ppm Remark Skin		1000 ppm	
Local name Oxyde de diméthyle # Dimethylether OEL TWA 1920 mg/m³ 1000 ppm Regulatory reference Norinkfljk besluit/Arrêté royal 16/11/2023 EU - Indicative Occupational Exposure Limit (IOEL) Toelly I acetate Local name n-Butyl acetate IOEL TWA 421 mg/m³ 10EL STEL 723 mg/m³ 10EL STEL 723 mg/m³ Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Bolgium - Occupational Exposure Limits COMMISSION DIRECTIVE (EU) 2019/1831 Local name Acétate de n-butyle # n-Butylacetaat OEL TWA 238 mg/m³ 50 ppm 50 ppm Regulatory reference Korinkfljk besluit/Arrête royal 18/11/2023 Regulatory reference Korinkfljk besluit/Arrête royal 18/11/2023 1-methoxy-2-propanol; monopropylene glyco methyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL) 100 ppm IOEL TWA 375 mg/m³ IOEL TWA 369 mg/m³ IOEL STEL 568 mg/m³ IOEL STEL 569 mg/m³ IOEL STEL <td< td=""><td>Regulatory reference</td><td>COMMISSION DIRECTIVE 2000/39/EC</td></td<>	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
OEL TWA 1920 mg/m² Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 IN Judicated (123-86-4) EU - Indicative Occupational Exposure Limit (IOEL TWA (100 mg/m²) DOEL TWA 241 mg/m² 100 ppm 100 ppm Regulatory reference 723 mg/m² Regulatory reference 724 mg/m² Regulatory reference MoMission DIRECTIVE (EU) 2019/1831 Belgium - Occupational Exposure Limits 28 mg/m² Local name Acétate de n-butyle # n-Butylacetaat OEL TWA 238 mg/m² 50 ppm OEL STEL 712 mg/m² 150 ppm Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 1-methoxy-2-propanol; monopropylene glycolomethyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 1 Methoxypropanol-2 IOEL TWA 375 mg/m² IOEL TWA 568 mg/m² IOEL Typerence CoMMission DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits CoMmission DIRECTIVE 2000/39/EC Belgium - Occupational Exposure L	Belgium - Occupational Exposure Limits		
Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 n-butyl acetate (123-86-4) EU - Indicative Occupational Exposure Limit (IOEL) Local name n-butyl acetate IOEL TWA 241 mg/m² 50 ppm 50 ppm IOEL STEL 723 mg/m² Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Bolgium - Occupational Exposure Limits Local name Acétate de n-butyle # n-Butylacetaat OEL TWA 238 mg/m² 50 ppm 50 ppm OEL STEL 712 mg/m² 150 ppm 150 ppm Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL) EU - Indicative Occupational Exposure Limit (IOEL) LOcal name 1-Methoxyropropanol-2 IOEL TWA 568 mg/m² 150 ppm Remark Six Regulatory reference Kominsision Directive 2000/39/EC Belgium - Occupational Exposure Limits Indéfinory-2-propanol # 1-Methoxy-2-propa	Local name	Oxyde de diméthyle # Dimethylether	
Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 n-butyl acetate (123-86-4) EU - Indicative Occupational Exposure Limit (IOEL) Local name n-Butyl acetate IOEL TWA 241 mg/m² 60 ppm 60 ppm Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Bolgium - Occupational Exposure Limits 238 mg/m² EL TWA 238 mg/m² 50 ppm 50 ppm OEL STEL 712 mg/m² 150 ppm 150 ppm Regulatory reference 150 ppm Regulatory reference 1 methoxy-2-propanol; monopropylene glycoriality bestult/Arrêté royal 16/11/2023 1-methoxy-2-propanol; monopropylene glycoriality (IOEL) 1 methoxy-2-propanol-2 Local name 1 -Methoxyropanol-2 IOEL TWA 375 mg/m² IOEL STEL 568 mg/m² IOEL STEL 568 mg/m² IOEL STEL 568 mg/m² Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits 1 mg/	OEL TWA	1920 mg/m³	
In-butyl acetate (123-86-4) EU - Indicative Occupational Exposure Limit (IOEL) Local name n-Butyl acetate IOEL TWA 241 mg/m² 50 ppm 50 ppm Regulatory reference CMMISSION DIRECTIVE (EU) 2019/1831 Regulatory reference Acétate de n-butyle # n-Butylacetaat OEL TWA 283 mg/m³ 50 ppm OEL STEL 712 mg/m² 150 ppm Regulatory reference Acétate de n-butyle # n-Butylacetaat OEL STEL 712 mg/m² 150 ppm Regulatory reference Acétate de n-butyle # n-Butylacetaat Regulatory reference Acétate de n-butyle # n-Butylacetaat OEL STEL 712 mg/m² 150 ppm Acétate de n-butyle # n-Butylacetaat 1-methoxy-2-propanol; monopropylene glyce Acétate de n-butyle # n-Butylacetaat 1-methoxy-2-propanol; monopropylene glyce Acétate de n-butyle # n-Butylacetaat 1-methoxy-2-propanol; monopropylene glyce Bel - Indicative Occupational Exposure Limit (IOEL) Local name 1-Methoxy-propanol-2 100 ppm 100 ppm		1000 ppm	
EU - Indicative Occupational Exposure Limit (IOEL) Local name n-Butyl acetate IOEL TWA 241 mg/m³ 50 ppm 50 ppm IOEL STEL 23 mg/m³ Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Belgium - Occupational Exposure Limits Acétate de n-butyle # n-Butylacetaat COEL TWA 238 mg/m³ 60 ppm OEL STEL 712 mg/m³ 150 ppm Regulatory reference Korinklijk besluit/Arrêté royal 16/11/2023 1-methoxy-2-propanol; monopropylene glycoloridade (Popularia) methyl efter (107-98-2) EU - Indicative Occupational Exposure Limit (OEL) 1-Methoxyropanol-2 Local name 1-Methoxyropanol-2 IOEL TWA 375 mg/m³ 100 ppm Regulatory reference 568 mg/m³ Regulatory reference CoMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limit (Popularia) Methoxyr-2-propanol # 1-Methoxyr-2-propanol Belgium - Occupational Exposure Limit (Popularia) 50 ppm OEL TWA 1-Methoxyr-2-propanol # 1-Methoxyr-2-propanol OE STEL	Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
Local name n-Butyl acetate IOEL TWA 241 mg/m³ IOEL STEL 23 mg/m³ IOEL STEL 723 mg/m³ Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Bolgium - Occupational Exposure Limits Acetate de n-butyle # n-Butylacetaat COEL TWA 238 mg/m³ 50 ppm OEL STEL 712 mg/m³ 150 ppm Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 1-methoxy-2-propanol; monopropylene glycolor methyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (OEL) The Methoxy-2-propanol-2 Local name 1-Methoxypropanol-2 IOEL TWA 375 mg/m³ 100 ppm 150 ppm Remark Se8 mg/m³ Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limit occupational Exposure Limits William (1)	n-butyl acetate (123-86-4)		
Page	EU - Indicative Occupational Exposure Limit (IOEL)		
Figure F	Local name	n-Butyl acetate	
DEL STEL 723 mg/m³ Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Belgium - Occupational Exposure Limits Acétate de n-butyle # n-Butylacetaat DEL TWA 238 mg/m³ 50 ppm 50 ppm DEL STEL 712 mg/m³ 150 ppm 150 ppm Regulatory reference Koninklijk bestuit/Arrêté royal 16/11/2023 Turethoxy-2-propanol; monopropylene glycolor bethyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 1-Methoxypropanol-2 IOEL TWA 375 mg/m³ 100 ppm IOEL STEL 588 mg/m³ 100 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL TWA 369 mg/m³	IOEL TWA	241 mg/m³	
Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Belgium - Occupational Exposure Limits Local name Acétate de n-butyle # n-Butylacetaat OEL TWA 238 mg/m³ 50 ppm 50 ppm OEL STEL 712 mg/m³ Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 Tuenthoxy-2-propanol; monopropylene glyco* methyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL**) Local name 1-Methoxypropanol-2 IOEL TWA 375 mg/m³ IOEL STEL 568 mg/m³ IOEL STEL 568 mg/m³ Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³		50 ppm	
Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831 Belgium - Occupational Exposure Limits Local name Acétate de n-butyle # n-Butylacetaat OEL TWA 238 mg/m³ 50 ppm 712 mg/m³ 150 ppm 150 ppm Regulatory reference Koninklijk beskuit/Arrêté royal 16/11/2023 1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) 1 methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL) 1 methoxy-propanol-2 Local name 1 - Methoxypropanol-2 IOEL TWA 375 mg/m³ 100 ppm IOEL STEL 568 mg/m³ 150 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits COMMISSION DIRECTIVE 2000/39/EC Local name 1 - Méthoxy-2-propanol # 1 - Methoxy-2-propanol OEL TWA 164 mg/m³ 50 ppm OEL STEL 369 mg/m³	IOEL STEL	723 mg/m³	
Belgium - Occupational Exposure Limits Local name Acétate de n-butyle # n-Butylacetaat OEL TWA 238 mg/m³ 50 ppm 50 ppm OEL STEL 712 mg/m³ 150 ppm 150 ppm Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 1-methoxy-2-propanol; monopropylene glycov methyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 1-Methoxypropanol-2 IOEL TWA 375 mg/m³ 100 ppm IOEL STEL 568 mg/m³ Remark Skin Regulatory reference CoMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³		150 ppm	
Local name Acétate de n-butyle # n-Butylacetaat OEL TWA 238 mg/m³ 50 ppm 50 ppm OEL STEL 712 mg/m³ Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 EU - Indicative Occupational Exposure Limit (IOEL) EU - Indicative Occupational Exposure Limit (IOEL) Local name 1-Methoxypropanol-2 IOEL TWA 375 mg/m³ 100 ppm IOEL STEL 568 mg/m³ Regulatory reference Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³	Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831	
OEL TWA 238 mg/m³ 50 ppm 50 ppm OEL STEL 712 mg/m³ 150 ppm 150 ppm Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 EU - Indicative Occupational Exposure Limit (IOEL) Tuber (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 1-Methoxypropanol-2 IOEL TWA 375 mg/m³ 100 ppm IOEL STEL 568 mg/m³ 150 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³	Belgium - Occupational Exposure Limits		
DEL STEL 712 mg/m³ Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 EU - Indicative Occupational Exposure Limit (IOEL TWA) 1-Methoxypropanol-2 Local name 1-Methoxypropanol-2 IOEL TWA 375 mg/m³ 100 pm IOEL STEL 568 mg/m³ 150 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³	Local name	Acétate de n-butyle # n-Butylacetaat	
OEL STEL 712 mg/m³ 150 ppm Regulatory reference Koninklijk besluit/Arrêté royal 16/11/2023 1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 1-Methoxypropanol-2 IOEL TWA 375 mg/m³ 100 ppm Remark 568 mg/m³ Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³	OEL TWA	238 mg/m³	
Regulatory reference Soninklijk besluit/Arrêté royal 16/11/2023 Temethoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name		50 ppm	
Regulatory reference **Noninklijk besluit/Arrêté royal 16/11/2023 **Innethoxy-2-propanol; monopropylene glyco' methyl ether (107-98-2) **EU - Indicative Occupational Exposure Limit (IOEL) Local name 1-Methoxypropanol-2 10EL TWA 375 mg/m³ 100 ppm 10EL STEL 568 mg/m³ 150 ppm Remark Regulatory reference COMMISSION DIRECTIVE 2000/39/EC **Belgium - Occupational Exposure Limits** Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol 0EL TWA 0 ppm 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol 0EL TWA 369 mg/m³ 360 ppm 0EL STEL 0 ppm 369 mg/m³	OEL STEL	712 mg/m³	
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name		150 ppm	
EU - Indicative Occupational Exposure Limit (IOEL) Local name 1-Methoxypropanol-2 IOEL TWA 375 mg/m³ 100 ppm IOEL STEL 568 mg/m³ 150 ppm Remark Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 369 mg/m³ 50 ppm	Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
Local name 1-Methoxypropanol-2 IOEL TWA 375 mg/m³ 100 ppm IOEL STEL 568 mg/m³ Remark 5kin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³	1-methoxy-2-propanol; monopropylene glyco	l methyl ether (107-98-2)	
10EL TWA 375 mg/m³ 100 ppm 100 ppm 150 ppm 1	EU - Indicative Occupational Exposure Limit (IOEL)		
100 ppm 100 ppm 100 ppm 150	Local name	1-Methoxypropanol-2	
IOEL STEL 568 mg/m³ 150 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³	IOEL TWA	375 mg/m³	
Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³		100 ppm	
Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³	IOEL STEL	568 mg/m³	
Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³		150 ppm	
Belgium - Occupational Exposure Limits Local name	Remark	Skin	
Local name 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
OEL TWA 184 mg/m³ 50 ppm OEL STEL 369 mg/m³	Belgium - Occupational Exposure Limits		
50 ppm OEL STEL 369 mg/m³	Local name	1-Méthoxy-2-propanol # 1-Methoxy-2-propanol	
OEL STEL 369 mg/m³	OEL TWA	184 mg/m³	
		50 ppm	
100 ppm	OEL STEL	369 mg/m³	
		100 ppm	

Safety Data Sheet

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
2-methoxy-1-methylethyl acetate (108-65-6)		
EU - Indicative Occupational Exposure Limit (IOE	EL)	
Local name	2-Methoxy-1-methylethylacetate	
IOEL TWA	275 mg/m³	
	50 ppm	
IOEL STEL	550 mg/m³	
	100 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Belgium - Occupational Exposure Limits		
Local name	Acétate de 2-(1-méthoxy)propyle # 2-(1-Methoxy)propylacetaat	
OEL TWA	275 mg/m³	
	50 ppm	
OEL STEL	550 mg/m³	
	100 ppm	
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
acetone; propan-2-one; propanone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOE	EL)	
Local name	Acetone	
IOEL TWA	1210 mg/m³	
	500 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Belgium - Occupational Exposure Limits		
Local name	Acétone # Aceton	
OEL TWA	594 mg/m³	
	246 ppm	
OEL STEL	1187 mg/m³	
	492 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

DNEL and PNEC

dimethyl ether (115-10-6)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, inhalation	1894 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects, inhalation	471 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0,155 mg/l	
PNEC aqua (marine water)	0,016 mg/l	
PNEC aqua (intermittent, freshwater)	1549 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0,681 mg/kg dwt	
PNEC sediment (marine water)	0,069 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,045 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	160 mg/l	
n-butyl acetate (123-86-4)		
PNEC (Water)		
PNEC aqua (freshwater)	0,18 mg/l	
PNEC aqua (marine water)	0,018 mg/l	
PNEC aqua (intermittent, freshwater)	0,36 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0,981 mg/kg dwt	
PNEC sediment (marine water)	0,0981 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,0903 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	35,6 mg/l	
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	553,5 mg/m³	
Acute - local effects, inhalation	553,5 mg/m³	
Long-term - systemic effects, dermal	183 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	369 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	33 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	43,9 mg/m³	
Long-term - systemic effects, dermal	78 mg/kg bodyweight/day	

Safety Data Sheet

1-methoxy-2-propanol; monopropylene glyco	ol methyl ether (107-98-2)		
PNEC (Water)	PNEC (Water)		
PNEC aqua (freshwater)	10 mg/l		
PNEC aqua (marine water)	1 mg/l		
PNEC aqua (intermittent, freshwater)	100 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	52,3 mg/kg dwt		
PNEC sediment (marine water)	5,2 mg/kg dwt		
PNEC (Soil)			
PNEC soil	4,59 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant	100 mg/l		
2-methoxy-1-methylethyl acetate (108-65-6)			
DNEL/DMEL (Workers)			
Acute - local effects, inhalation	550 mg/m³		
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	275 mg/m³		
DNEL/DMEL (General population)			
Acute - systemic effects, oral	500 mg/kg bodyweight/day		
Long-term - systemic effects,oral	36 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	33 mg/m³		
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day		
Long-term - local effects, inhalation	33 mg/m³		
PNEC (Water)			
PNEC aqua (freshwater)	0,635 mg/l		
PNEC aqua (marine water)	0,0635 mg/l		
PNEC aqua (intermittent, freshwater)	6,35 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	3,29 mg/kg dwt		
PNEC sediment (marine water)	0,329 mg/kg dwt		
PNEC (Soil)			
PNEC soil	0,29 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant	100 mg/l		
acetone; propan-2-one; propanone (67-64-1)			
DNEL/DMEL (Workers)			
Acute - local effects, inhalation	2420 mg/m³		
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day		
	1210 mg/m³		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetone; propan-2-one; propanone (67-64-1)		
62 mg/kg bodyweight/day		
200 mg/m³		
62 mg/kg bodyweight/day		
10,6 mg/l		
1,06 mg/l		
21 mg/l		
PNEC (Sediment)		
30,4 mg/kg dwt		
3,04 mg/kg dwt		
PNEC (Soil)		
29,5 mg/kg dwt		
PNEC (STP)		
100 mg/l		

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protection equipment

Personal protective equipment symbol(s):





Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Butyl-rubber protective gloves.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Blue.

Appearance : DME propelled liquid.

Odour : Solvent.

Odour threshold : Not available

Melting point : Not applicable

Freezing point : Not available

Boiling point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Lower explosion limit : Not available
Upper explosion limit : Not available
Flash point : -18 °C (closed cup)

Auto-ignition temperature : > 200 °C Decomposition temperature : Not available : Not applicable : < 1 mm²/s Viscosity, kinematic Solubility : Insoluble in water. Partition coefficient n-octanol/water (Log Kow) : Not applicable Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : 0,87 g/cm3 at 20 °C Relative density : Not available Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

Information with regard to physical hazard classes

% of flammable ingredients : 75 – 100 %

Other safety characteristics

VOC content : 785 g/l

Additional information : For aerosols data for the product without propellant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on h		finad in Danulatian	/EC\ N. 4070/0000
11 1 Information on r	iazaro ciasses as de	tinea in Realliation	TECH NO 17/7/2008

Acute toxicity (oral): Not classified (Based on available data, the classification criteria are not met)Acute toxicity (dermal): Not classified (Based on available data, the classification criteria are not met)Acute toxicity (inhalation): Not classified (Based on available data, the classification criteria are not met)

dimethyl ether (115-10-6)	
LC50 Inhalation - Rat	308,5 mg/l/4h
LC50 Inhalation - Rat [ppm]	164000 ppm
n-butyl acetate (123-86-4)	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 17600 mg/kg

LC50 Inhalation - Rat (Dust/Mist)	23,4 mg/l/4h
1-methoxy-2-propanol: monopropylene glyco	l methyl ether (107-98-2)

LD50 oral rat	4016 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 25,8 mg/l

2-methoxy-1-methylethyl acetate (108-65-6)

LC50 Inhalation - Rat

LD50 oral rat	> 5000 mg/kg
LD50 oral	8532 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
LD50 dermal	> 5000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 10800 mg/l

1-Naphthalenesulfonic acid, 6-diazo-5,6-dihydro-5-oxo-, ester with phenyl(2,3,4-trihydroxyphenyl)methanone (68510-93-0)

LD50 oral rat > 5000 mg/kg bodyweight

C.I. Basic Violet 3; 4-[4,4'-bis(dimethylamino) benzhydrylidene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium chloride (548-62-9)

LD50 oral rat	670 mg/kg			
LD50 dermal rabbit	> 2000 mg/kg			
acetone; propan-2-one; propanone (67-64-1)				
LD50 oral rat	5800 mg/kg bodyweight			
LD50 dermal	> 15688 mg/kg bodyweight			

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)

pH: Not applicable

76 mg/l/4h

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amen	ded by Regulation (EU) 2020/878			
n-butyl acetate (123-86-4)				
рН	6,2			
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable			
n-butyl acetate (123-86-4)				
рН	6,2			
Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity	 : Not classified (Based on available data, the classification criteria are not met) : Not classified (Based on available data, the classification criteria are not met) : Not classified (Based on available data, the classification criteria are not met) 			
C.I. Basic Violet 3; 4-[4,4'-bis(dimethylamin (548-62-9)	no) benzhydrylidene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium chloride			
NOAEL (chronic, oral, animal/male, 2 years)	225 mg/kg bodyweight			
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight			
Reproductive toxicity STOT-single exposure	Not classified (Based on available data, the classification criteria are not met)May cause drowsiness or dizziness.			
n-butyl acetate (123-86-4)				
STOT-single exposure	May cause drowsiness or dizziness.			
1-methoxy-2-propanol; monopropylene gl	ycol methyl ether (107-98-2)			
STOT-single exposure	May cause drowsiness or dizziness.			
2-methoxy-1-methylethyl acetate (108-65-6	5)			
STOT-single exposure May cause drowsiness or dizziness.				
acetone; propan-2-one; propanone (67-64-	-1)			
STOT-single exposure	May cause drowsiness or dizziness.			
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)			
n-butyl acetate (123-86-4)				
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight			
NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight				
1-methoxy-2-propanol; monopropylene gl	ycol methyl ether (107-98-2)			
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight			
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight			
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight			
2-methoxy-1-methylethyl acetate (108-65-6	3)			
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight			
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)			
POSITIV 20				
Vaporizer	Aerosol			
Viscosity, kinematic	< 1 mm²/s			
n-butyl acetate (123-86-4)				
Viscosity, kinematic	0,83 mm²/s			
1-methoxy-2-propanol; monopropylene gl	ycol methyl ether (107-98-2)			
Viscosity, kinematic	1,848 mm²/s			

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short–term (acute)

: Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic)

: Harmful to aquatic life with long lasting effects.

(GIIOIIIC)				
dimethyl ether (115-10-6)				
LC50 - Fish [1]	> 4,1 g/l			
EC50 - Crustacea [1]	> 4,4 g/l Daphnia magna (Water flea)			
EC50 96h - Algae [1]	154917 mg/l			
n-butyl acetate (123-86-4)				
LC50 - Fish [1]	18 mg/l			
EC50 - Crustacea [1]	44 mg/l			
EC50 72h - Algae [1]	674,7 mg/l			
LOEC (chronic)	47,6 mg/l			
NOEC (chronic)	23,2 mg/l			
NOEC chronic algae	200 mg/l			
1-methoxy-2-propanol; monopropylene	e glycol methyl ether (107-98-2)			
LC50 - Fish [1]	6812 mg/l			
LC50 - Fish [2]	20800 mg/l			
EC50 - Crustacea [1]	21100 – 25900 mg/l			
EC50 - Other aquatic organisms [1]	2954 mg/l			
ErC50 algae	> 1000 mg/l			
2-methoxy-1-methylethyl acetate (108-	65-6)			
LC50 - Fish [1]	> 100 mg/l			
EC50 - Crustacea [1]	> 500 mg/l			
EC50 - Other aquatic organisms [1]	408 mg/l			
EC50 - Other aquatic organisms [2]	> 1000 mg/l			
EC50 72h - Algae [1]	> 1000 mg/l			
NOEC (chronic)	≥ 100 mg/l			
NOEC chronic fish	47,5 mg/l			

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-Naphthalenesulfonic acid, 6-diazo-5	,6-dihydro-5-oxo-, ester with phenyl(2,3,4-trihydroxyphenyl)methanone (68510-93-0)		
LC50 - Fish [1]	- Fish [1] 22 – 50 mg/l		
EC50 - Crustacea [1]	13,78 mg/l Daphnia magna (Water flea)		
EC50 72h - Algae [1]	12 mg/l		
C.I. Basic Violet 3; 4-[4,4'-bis(dimethyl (548-62-9)	amino) benzhydrylidene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium chloride		
LC50 - Fish [1]	0 - Fish [1] 0,082 mg/l		
EC50 - Crustacea [2]	0,53 mg/l Daphnia magna (Water flea)		
EC50 72h - Algae [1]	0,21 mg/l		
acetone; propan-2-one; propanone (6	7-64-1)		
LC50 - Fish [1]	5540 mg/l		
EC50 - Other aquatic organisms [1]	12600 mg/l Daphnia magna (Water flea)		
LOEC (chronic)	> 79 mg/l		
NOEC (chronic)	≥ 79 mg/l		

POSITIV 20	
Persistence and degradability	Not established. No data is available on the degradability of this product.

12.3. Bioaccumulative potential

POSITIV 20				
artition coefficient n-octanol/water (Log Kow) Not applicable				
dimethyl ether (115-10-6)				
Partition coefficient n-octanol/water (Log Pow)	0,07			
n-butyl acetate (123-86-4)				
Partition coefficient n-octanol/water (Log Pow)	2,3			
1-methoxy-2-propanol; monopropylene glyco	ol methyl ether (107-98-2)			
Bioconcentration factor (BCF REACH) < 100				
Partition coefficient n-octanol/water (Log Pow)	0,37			
2-methoxy-1-methylethyl acetate (108-65-6)				
Partition coefficient n-octanol/water (Log Pow)	1,2			
C.I. Basic Violet 3; 4-[4,4'-bis(dimethylamino) (548-62-9)	benzhydrylidene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium chloride			
Partition coefficient n-octanol/water (Log Pow)	1,172			
acetone; propan-2-one; propanone (67-64-1)				
Partition coefficient n-octanol/water (Log Pow)	-0,24			

12.4. Mobility in soil

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment

POSITIV 20

Results of PBT assessment Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

POSITIV 20

PO3111V 20		
Other information	No other effects known	
Global warming potential (GWP)	0.40 (Fluorinated greenhouse gases - (EC) No 2024/573)	

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods European List of Waste (LoW, EC 2000/532)

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	umber			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard	class(es)			
2.1	2.1	2.1	2.1	2.1
2	2	2	2	2
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
5. Environmental ha	azards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11 Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR): MP9Transport category (ADR): 2Special provisions for carriage - Packages (ADR): V14Special provisions for carriage - Loading, unloading: CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN)

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

: 1

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

28/08/2024 (Revision date) BE - en 16/20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List < 0.1% or SCL: [4-[4,4'-bis(dimethylamino) benzhydrylidene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium chloride (C.I. Basic Violet 3) (EC 208-953-6, CAS 548-62-9).

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 785 g/l

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes				
Section	Changed item	Comments		
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified		
2.2	Precautionary statements (CLP)	Modified		
2.2	Hazard statements (CLP)	Modified		
2.2	Hazard pictograms (CLP)	Modified		
9		Modified		

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	

Safety Data Sheet

Abbreviations and acronyms:		
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disruptor	

Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aerosol 1	Aerosol, Category 1	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Carc. 2	Carcinogenicity, Category 2	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1	Flammable gases, Category 1	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Flam. Sol. 1	Flammable solids, Category 1	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
Self-react. C	Self-Reactive Substances and Mixtures, Type C	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H228	Flammable solid.	
H229	Pressurised container: May burst if heated.	
H242	Heating may cause a fire.	
H280	Contains gas under pressure; may explode if heated.	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H336	May cause drowsiness or dizziness.	
H351	Suspected of causing cancer.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.