



SINGLE BUILT-IN CHARGER

USB-C™ 45 W

The Single USB-C™ Charger provides powerful and fast charging power via USB Power Delivery with up to 45 watts - in caravans, boats and motorhomes.

With the practical, symmetrical USB-C™ connector becoming the standard port of the future, the charger already establishes your top-speed charging platform today.

FEATURES

- Via USB-C™ port with USB Power Delivery provides 45 watts for extremely powerful and fast charging
- Charges smartphones 30 % faster than comparable products from other manufacturers
- Charges smartphones 50 % faster than products with a USB-A port from other manufacturers
- Easy to install and compatible with Berker and Inprojal switch ranges
- Suitable for wall thicknesses up to 17 mm
- Safe due to rounded edges, protection against short circuits, overvoltage, high temperatures. Dust protection optional.
- With Tyco plug or open cable ends with 200 mm cable each

VARIANTS


ITEM	60375 ●	60376 ●
MODEL	WTS-E 1 C QC 3 PD 45 W + Tyco connector	WTS-E 1 C QC 3 PD 45 W
INSTALLATION	with Tyco connector no. 180908	with open ends, tin-plated
CABLE LENGTH	200 mm	200 mm

TECHNICAL DATA

OUTPUT POWER	45 W
CURRENT IN STAND-BY MODE	≤ 2 mA
NOMINAL INPUT VOLTAGE	12 - 24 V ===
DIMENSIONS	Ø front: 36 mm, Ø chassis: 27 mm, depth: 44.5 mm
WEIGHT	25 g
OPERATING TEMPERATURE	-20 °C - +70 °C
STORAGE TEMPERATURE	-40 °C - +90 °C
COMPATIBLE	with most smartphones, tablets and notebooks that support USB Power Delivery or Quick Charge
STANDARDS AND CERTIFICATIONS	CE, UKCA EN 55032:2015, EN 55035:2017, EN 50498:2011 RoHS, REACH ECE-R10 Type Approval FMVSS 201 (compliance tests - Upper Interior Head Impact Protection)



CONNECTION AND FAST-CHARGING TECHNOLOGY

	USB-C™  reversible connector										
TOTAL POWER	<table border="0"> <tr> <td>5.0 V ===</td> <td>max. 3.0 A (15 W)</td> </tr> <tr> <td>9.0 V ===</td> <td>max. 2.0 A (18 W)</td> </tr> <tr> <td>12.0 V ===</td> <td>max. 3.0 A (36 W)</td> </tr> <tr> <td>15.0 V ===</td> <td>max. 3.0 A (45 W)</td> </tr> <tr> <td>20.0 V ===</td> <td>max. 2.25 A (45 W)</td> </tr> </table>	5.0 V ===	max. 3.0 A (15 W)	9.0 V ===	max. 2.0 A (18 W)	12.0 V ===	max. 3.0 A (36 W)	15.0 V ===	max. 3.0 A (45 W)	20.0 V ===	max. 2.25 A (45 W)
5.0 V ===	max. 3.0 A (15 W)										
9.0 V ===	max. 2.0 A (18 W)										
12.0 V ===	max. 3.0 A (36 W)										
15.0 V ===	max. 3.0 A (45 W)										
20.0 V ===	max. 2.25 A (45 W)										
FAST-CHARGING TECHNOLOGY	PD 3.0 QC 4.0 QC 3.0 QC 2.0 FCP DCP BC 1.2 AFC SCP PE 1.1 SFCP										
LIFETIME IN INSERTION AND REMOVAL CYCLES	approx. 10,000										