


Complementary power Darlington transistors



Features


- Good h_{FE} linearity
- High f_T frequency
- Monolithic Darlington configuration with integrated antiparallel collector-emitter diode

Application

- Audio amplifiers
- Linear and switching industrial equipment

Description

These devices are manufactured in planar technology with “base island” layout and monolithic Darlington configuration.



Product status links

[BDX53B](#)

[BDX53C](#)

[BDX54C](#)

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value		Unit
		NPN	BDX53B	
		PNP	BDX53C	
V_{CBO}	Collector-base voltage ($I_E = 0$ A)		80	V
V_{CEO}	Collector-emitter voltage ($I_B = 0$ A)		80	V
V_{EBO}	Collector-base voltage ($I_C = 0$ A)		5	V
I_C	Collector current		8	A
I_{CM}	Collector peak current		12	A
I_B	Base current		0.2	A
P_{TOT}	Total power dissipation at $T_C = 25$ °C		60	W
T_{stg}	Storage temperature range		-65 to 150	°C
T_J	Maximum operating junction temperature		150	°C

Note: For PNP types voltage and current values are negative.

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance, junction-to-case	2.08	°C/W

2 Electrical characteristics

$T_C = 25\text{ °C}$ unless otherwise specified.

Table 3. Electrical characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{CBO}	Collector cut-off current	$V_{CB} = 80\text{ V}$, $I_E = 0\text{ A}$ for BDX53B	-	-	0.2	mA
		$V_{CB} = 100\text{ V}$, $I_E = 0\text{ A}$ for BDX53C, BDX54C	-	-	0.2	mA
I_{CEO}	Collector cut-off current	$V_{CE} = 40\text{ V}$, $I_B = 0\text{ A}$ for BDX53B	-	-	0.5	mA
		$V_{CE} = 50\text{ V}$, $I_B = 0\text{ A}$ for BDX53C, BDX54C	-	-	0.5	mA
I_{EBO}	Emitter cut-off current	$V_{EB} = 5\text{ V}$, $I_C = 0\text{ A}$	-	-	2	mA
$V_{CEO(sus)}^{(1)}$	Collector-emitter sustaining voltage	$I_C = 100\text{ mA}$, $I_B = 0\text{ A}$ for BDX53B	80	-	-	V
		$I_C = 100\text{ mA}$, $I_B = 0\text{ A}$ for BDX53C, BDX54C	100	-	-	V
$V_{CE(sat)}^{(1)}$	Collector-emitter saturation voltage	$I_C = 3\text{ A}$, $I_B = 12\text{ mA}$	-	-	2	V
$V_{BE(sat)}^{(1)}$	Base-emitter saturation voltage	$I_C = 3\text{ A}$, $I_B = 12\text{ mA}$	-	-	2.5	V
$h_{FE}^{(1)}$	DC current gain	$I_C = 3\text{ A}$, $V_{CE} = 3\text{ V}$	750	-	-	-
$V_F^{(1)}$	Diode forward voltage	$I_F = 3\text{ A}$	-	1.8	2.5	V
		$I_F = 8\text{ A}$	-	2.5	-	V

1. Pulse test: pulse duration = 300 μs , duty cycle 1.5 %.


Note: For PNP types voltage and current values are negative.

3 Package information

To meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

3.1 TO-220 type A package information

Figure 1. TO-220 type A package outline



0015988_typeA_Rev_24

Table 4. TO-220 type A package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
b	0.61		0.88
b1	1.14		1.55
c	0.48		0.70
D	15.25		15.75
D1		1.27	
E	10.00		10.40
e	2.40		2.70
e1	4.95		5.15
F	1.23		1.32
H1	6.20		6.60
J1	2.40		2.72
L	13.00		14.00
L1	3.50		3.93
L20		16.40	
L30		28.90	
øP	3.75		3.85
Q	2.65		2.95
Slug flatness		0.03	0.10



4 Ordering information

Table 5. Order codes

Order codes	Marking	Polarity	Package	Packing
BDX53B	BDX53B	NPN	TO-220	Tube
BDX53C	BDX53C	NPN		
BDX54C	BDX54C	PNP		

Revision history

Table 6. Document revision history

Date	Revision	Changes
23-Oct-2007	4	Technology change from epibase to planar (PCN APMPWR/07/2417 and APM-PWR/07/2615)
17-Jul-2025	5	Removed order code BDX54B. Updated Table 1. Absolute maximum ratings and Section 3: Package information . Minor text changes.



Contents

1	Electrical ratings	2
2	Electrical characteristics.....	3
3	Package information.....	4
3.1	TO-220 type A package information	4
4	Ordering information	6
	Revision history	7

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice.

In the event of any conflict between the provisions of this document and the provisions of any contractual arrangement in force between the purchasers and ST, the provisions of such contractual arrangement shall prevail.

The purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

The purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of the purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

If the purchasers identify an ST product that meets their functional and performance requirements but that is not designated for the purchasers' market segment, the purchasers shall contact ST for more information.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2025 STMicroelectronics – All rights reserved